

Formula & Proto

HILLCLIMB

GUIDE

Compound	HCW	637	HC2	A15	HC3	840	HC4	315	HC5	046
Warm Up	Immediate	Immediate	Immediate	~1km	>1km					
Conditions	Wet	Dry / Damp	Dry / Warm	Dry / Warm	Dry / Warm					
Recommended Hillclimb Length	All	0km > < 3km	0km > < 5km	3km > < 14km	5km > < 14km					
Recommended Tread Temperature Range	10° > < 45°C	20°C > < 60°C	35°C > < 80°C	35°C > < 90°C	40°C > < 90°C					
Recommended Ambient Temperature Range	All	0°C > < 25°C	15°C > < 35°C	15°C > < 40°C	20°C > < 40°C					
Grip Level	Very High	High	Very High	High	High					
Construction	Wet	Slick	Slick	Slick	Slick					

COMPOUND	CONDITIONS			AMBIENT TEMP (°C)									
	WET	DAMP	DRY	0	5	10	15	20	25	30	35	40	
HC5													
HC4													
HC3													
HC2													
HCW													

SIZE	RIM RANGE	DIAMETER (mm)	CIRCUMFERENCE (mm)	SECTION (mm)	TREAD (mm)
180/550R13	8.0 - 9.5	554	1740	241	184
195/530R13	8.0 - 9.0	528	1659	246	207
210/550R13	9.0 - 10.0	554	1740	269	210
230/550R13	9.0 - 11.0	554	1740	290	234
245/570R13	9.5 - 11.0	575	1806	287	253
250/570R13	10.0 - 11.0	575	1806	290	246
290/570R13	10.5 - 12.0	579	1819	317	282
245/600R13	10.0 - 11.0	600	1885	287	243
300/600R13	13.0 - 14.0	607	1907	372	301
315/660R13	13.0 - 15.0	654	2055	381	311
330/620R13	14.0 - 16.0	620	1948	388	343

NOVA

LICENSED MANUFACTURER OF

AVON
MOTORSPORT

Continuing the Avon Legacy

www.novamotorsport.com

GT & Saloon HILLCLIMB GUIDE



Compound	317	046	800
Warm Up	Immediate	<1km	>1km
Conditions	Wet	Dry	Dry
Recommended Hillclimb Length	All	0km > < 14km	5km > < 14km
Recommended Tread Temperature Range	15° > < 45°C	40°C > < 80°C	40°C > < 80°C
Recommended Ambient Temperature Range	All	10°C > < 30°C	20°C > < 40°C
Grip Level	Very High	Very High	Very High
Construction	Wet	Slick	Slick

COMPOUND	CONDITIONS			AMBIENT TEMP (° C)									
	WET	DAMP	DRY	0	5	10	15	20	25	30	35	40	
800													
046													
317													

SIZE	RIM RANGE	DIAMETER (mm)	CIRCUMFERENCE (mm)	SECTION (mm)	TREAD (mm)
200/605R17	7.0 - 8.0	610	1916	221	201
230/605R17	8.0 - 9.0	610	1916	250	234
210/640R18	7.0 - 8.5	648	2036	227	213
250/640R18	9.5 - 10.5	645	2026	284	251
270/650R18	10.0 - 11.0	655	2058	302	272
270/680R19	10.5 - 11.5	681	2139	291	268
300/650R18	11.0 - 12.5	653	2051	329	304
300/680R18	12.0 - 13.0	682	2143	330	305
320/705R18	13.0 - 14.0	704	2212	358	319
320/705R19	13.0 - 14.0	704	2212	358	319

NOVA

LICENSED MANUFACTURER OF

AVON
MOTORSPORT

Continuing the Avon Legacy
www.novamotorsport.com